

FULL-SLICK COMPETITION TIRE

The Proxes RS1 is a full-slick competition tire* that provides consistent performance throughout the life of the tire. This race tire is excellent in dry braking and built to endure closed-course road racing, time attack, track days, and high performance driving schools. Compound, construction, and design contribute to its durability, responsive handling, and high-speed performance in dry weather conditions.

*Warning: For racing purposes only. Not for highway use.

POPULAR FITMENTS

Camaro
Mustang
Nissan GT-R
Porsche GT-3

ADVANCED RAYON CASING

- Provides durability and stability at high speed.

HIGH-MODULUS BEAD FILLER AND STEEL REINFORCED SIDEWALL

- Provides crisp and responsive handling.
- Offers excellent steering response and feel.

DURABLE, RACE-PROVEN COMPOUND

- Contributes to excellent dry braking.
- Offers excellent wear resistance.
- Provides high grip levels across a wide temperature range.

SPIRAL WOUND CAP PLY

- Provides uniformity and consistency.



SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	OVERALL DIA. (IN.)**	OVERALL WIDTH (IN.)**	MAX LOAD (LBS)	MAX PRESSURE (PSI)	REVS PER MILE
18	245/640R18	SL	BSW	163460	(8.5)	25	25.4	9.8	N/A	N/A	818
	285/650R18	SL	BSW	171680	(10.0)	27	25.5	11.1	N/A	N/A	814
	285/680R18	SL	BSW	163450	10.0	31	26.7	11.7	N/A	N/A	778
	335/710R18	SL	BSW	171440	12.0	34	27.7	13.4	N/A	N/A	749

SPORTS CAR / COMPETITION

S

SETUP GUIDELINES

TOYO TIRES RECOMMENDS THE FOLLOWING GENERAL SETUP GUIDELINES FOR THE PROXES RS1:

- Operating Temperature: 160°F to 220°F
- Hot Inflation Pressures: High 30s to Low 40s (PSI)
- Camber: -2.5° to -5.0°
- Caster: As much positive as possible

*"SL" = Standard Load, "BSW" = Black Sidewall.
Bold designates measuring rim width. **Inflated dimensions.